

## Applicator Shanks



**All models feature poly rollers to reduce friction**

**No stretching tape**

(1) Roll Support + (1) Applicator Shank  
= (1) complete Drip Tape Applicator

Part numbers are itemized on price list

### Series 388

This shank integrates the Series 288 design with a heavy ripper shank. Use in any condition in which the soil is untilled or hard, perhaps with conservation tillage and planting practices. 20 PTO-HP rating per 40388 shank. 15 PTO-HP rating per 30388 shank. Features shear-bolt for shank protection. Maximum depth is 12" OR "plow depth" - the primary tillage layer.



#### Drip Tape Ripper Shank & Guide

**30388** -- for 3" square toolbar

**40388** -- for 4" square toolbar

**For deep placement below seedbed  
Maximum 12" depth**

### Series 592

This super-duty shank is designed for breaking below "plow depth" to place permanent drip tape below the tillage layer. Shank is rated at 50 PTO-HP per shank. Maximum depth is 18". Also use at 12" depth, for example, if this is below plow depth or if it is known high-HP equipment is needed to fracture your soil. Features shear-bolt for shank protection.



#### Drip Tape Ripper Shank & Guide

**60592** -- for 6" square toolbar

**70592** -- for 7" square toolbar

**For deep placement  
below plow level  
Maximum 18" depth**

Connectors turn on  
**THREE** rollers, arrayed  
on 10" circle