

## Toolbar Hitches

### Open-center hitch

MAIN HITCH TOOLBAR



### A-frame hitch



Two hitch designs. The Open-Center Hitch on \_\_70 Models supports the toolbar frame on each end. The center is fully open to place and adjust attachments without conflict with hitch parts. Bonus: The main hitch toolbar can be detached to use for other jobs.

The A-frame hitch on \_\_60 Models is the same hitch as on Bed Shapers and Mulch Lifters and supports the toolbar frame in the center. Hitch parts can be moved laterally to place and adjust attachments. This solid, efficient, low-cost design is ideal for dedicated equipment.

## Toolbar Frames

### 3-BAR TOOLBAR FRAME

Toolbars are welded into a 1-piece frame for rugged strength. 2000 Series Models feature 2" square toolbars and intended for Category-1 tractors - up to generally 50 HP. 4000 Series Models feature heavier 2-1/2" square toolbars and intended for Category-2 tractors - up to 80 HP. Toolbar spacing for both is 12".



### 4-BAR TOOLBAR FRAME

Frames with three toolbars offer sufficient space for most full-width cultivator set-ups. 4-bar frames tend to offer additional toolbar space to offset shanks, for more space between attachments or for more complex row crop set-ups. 5-bar frames add even more space and flexibility to your custom cultivator. Simple, low-HP 2-Toolbar Models are available in the Garden Series equipment.



## Models

Open-center hitch	2370	2470	2570	4470	4570
Open center hitch toolbar	3" square			4" square	
A-frame hitch	2360	2460	2560	4460	4560
Toolbar Size	2" square			2-1/2" square	
Toolbar Frame	3-bar	4-bar	5-bar	4-bar	5-bar

### Toolbar Frame Width

Add a suffix to Model to specify toolbar frame width. Example: 2370-84

	TOOLBAR FRAME WIDTH	MAXIMUM WORKING WIDTH	MAXIMUM TRACTOR WHEEL TRACK WIDTH
<b>-64</b>	64"	54"	54"
<b>-72</b>	72"	62"	62"
<b>-84</b>	84"	74"	74"
<b>-96</b>	96"	86"	86"

The working width of the toolbar frame should at least match the tractor wheel track width (measured center-to-center). Then the total toolbar width should be at least 10" wider than working width for full-width coverage of tillage attachments. Most Cultivator Models shown in Catalog include 72" or 84" Toolbar Frame Widths.



### Custom Toolbar Frames

- RIGID -- FLEX - HYDRAULIC FOLD**
- MULTI-BED EQUIPMENT**
- NO WIDER THAN TRACTOR**
- ANY SPECIALTY PURPOSE**